



Basic intro to Linux Kernel

... at least few bits of it

Vratislav Bendel

Principal Software Maintenance Engineer



What we'll cover today:

- ▶ Memory Management
High level overview
- ▶ Basic structs
Primitives you should know
- ▶ Basic debugging
So you won't get lost

Role of the kernel

... and it's scope

Role of the kernel

... and it's scope

- ▶ Interface between userspace and HW
- ▶ HW control
- ▶ Syscall interface
- ▶ Memory & process management

Memory Management

... just high level basics

What is memory?

Kernel's perspective

- ▶ Memory is addressed in blocks called “**pages**”
- ▶ A single **page size** depends on architecture:
 - x86 ~ 4 kB ppc64, s390 ~ 64 kB
- ▶ Kernel defines **memory zones**: DMA, DMA32, Normal **
- ▶ Contiguous memory is packed into blocks of higher **page order**,
 - up to order 10 [4MB of contiguous memory]

Kernel's memory

It's a program as any other, right?

The Linux kernel is itself a C program with its own structs and data. Therefore it itself requires to allocate memory.

- ▶ Kernel uses a concept called **"slabs"**, a.k.a. **"kernel memory caches"**
- ▶ A page block gets "split" into dedicated objects of specific size (for example *inode cache*, *dentry cache*, ...)
- ▶ Generic allocations via *kmalloc()* fall into *kmalloc-XX* slabs
- ▶ Large allocations (uncommon) fall to process-like *vmalloc*
- ▶ [/proc/slabinfo](#)

... more on the MM lecture

Memory “types”

Types by usage

- ▶ **Cache** memory
 - Data fetched from disk, stored in main memory for faster access
- ▶ **Anonymous** memory
 - Transient/working process data - structures, variables, ...
- ▶ **Kernel** memory
 - Slabs, per-cpu, page-tables – all kernel structures
- ▶ [/proc/meminfo](#)

Memory “types”

Process memory

- ▶ **Virtual** memory ← *can **overcommit***
Kernel “acks” process’ allocation and creates
a *Virtual Memory Area [VMA]*
- ▶ **Physical** memory
Data actually stored in Main RAM
RSS - Resident Set Size

Linux MM design

Page fault

Virtual addresses (process context) are **mapped** to physical addresses (in RAM). These mappings are stored in **“page tables”** and CPU caches them in the *Translation Lookaside Buffer [TLB]*.

- ▶ When a virtual-to-physical mapping does not exist, the CPU generates a HW exception **“page_fault”**
- ▶ Kernel handles the `page_fault` by allocating the physical page/s and creating the mapping.

Linux MM design

Lazy allocation scheme

Linux kernel utilizes a *lazy* allocation scheme:

- ▶ Processes are not allocating memory, they create virtual mappings
- ▶ Physical memory is allocated via `page_fault`, only once a virtual address is actually accessed (read or write)

Linux MM design

Allocation algorithm

Linux kernel is designed to utilize available resources.

- ▶ Physical allocations take 'free' memory page/s while available (*fast path*)
- ▶ Once 'free' memory is low (based on zone watermarks), the kernel needs to **reclaim** some memory back into the 'free' pool (*slow path*)

Reclaim ~ Either drop cached or swap out anon pages

Basic structures

Primitives you should get familiar with

Linked List

The bread and butter

Linux kernel uses a **doubly-linked list** primitive data structure:

- ▶ [include/linux/types.h](#)

```
struct list_head { struct list_head *next, *prev; };
```

- ▶ [include/linux/list.h](#)

```
LIST_HEAD[_INIT](name), list_empty() // head == next == prev
```

```
list_add(), list_add_tail(), list_del(), ... // LIST_POISON[1|2]
```

- ▶ List heads are **embedded** in associated structs

Hlist

Deletion efficiency

Hash lists are used when efficient deletion is preferred, like hash tables.

- ▶ [include/linux/types.h](#)

```
struct hlist_head { struct hlist_node *first; };
```

```
struct hlist_node { struct hlist_node *next, **pprev; };
```

- ▶ [include/linux/list.h](#)

```
HLIST_HEAD[_INIT](name)    INIT_HLIST_NODE(n)
```

```
hlist_empty(hlist-head *h) // h->first == NULL
```

```
hlist_add_head(), hlist_add_before(), hlist_del(), ... // LIST_POISON[1|2]
```

container_of()

Offset macro

The `container_of()` function macro is used to offset a pointer to the beginning/root of the structure, where the pointer is an embedded linking data structure, for example list, rb_tree node or other structures. Effectively it simply translates to assembly pointer arithmetic.

- ▶ `include/linux/container_of.h`

```
#define container_of(ptr, type, member)
```

@ptr: the pointer to the member.

@type: the type of the container struct this is embedded in.

@member: the name of the member within the struct.

Red-Black tree

When you need ordering

Red-Black tree structure is used when ordered lookup is needed. Optionally a variant with cached leftmost element for O(1) search.

- ▶ [include/linux/rbtree types.h](#)

```
struct rb_root {  
    struct rb_node *rb_node;  
};  
struct rb_root_cached {  
    struct rb_root rb_root;  
    struct rb_node *rb_leftmost; };
```

```
struct rb_node {  
    unsigned long __rb_parent_color;  
    struct rb_node *rb_right;  
    struct rb_node *rb_left;  
};
```

- ▶ rb_nodes are also **embedded** in associated structs.

Red-Black tree

When you need ordering

- ▶ General API implemented in:

lib/rbtree.c

```
void rb_insert_color(struct rb_node *node, struct rb_root *root)
```

```
void rb_erase(struct rb_node *node, struct rb_root *root)
```

- ▶ Although many subsystems implement their own customized functions.

Radix tree, Xarray, Maple tree

Lookup in huge datasets

Radix tree (oldest), *Xarray* and *Maple tree* are data structures used primarily to keep track of **process' address space VMAs** (incl. **pagecache**).

- ▶ Radix tree is a “*compressed trie*” which maps long integer keys to pointer values. It's good at storing huge datasets (address space), but has certain inconveniences, namely when sparsely populated.
- ▶ Xarray and Maple tree (newest) are special data structures implemented** specifically to tackle the problematics of storing address space and other similar data more efficiently.

Radix tree, Xarray, Maple tree

Lookup in huge datasets

- ▶ Radix tree: (being deprecated)

<https://lwn.net/Articles/175432/>

- ▶ Xarray:

<https://docs.kernel.org/core-api/xarray.html>

- ▶ Maple tree:

https://docs.kernel.org/core-api/maple_tree.html

void *abstractions & unions

Polymorphism

Certain structures may be used in different ways or different contexts or different subsystems, ...

- ▶ void* struct members are used for context-relative pointers
- ▶ C-lang unions define different uses of a given struct
- ▶ The code which works with the struct knows the context
- ▶ Commonly paired with specifying object types via flags members

void *abstractions & unions

Polymorphism

- ▶ Example excerpt: [include/linux/mm types.h](#)

```
struct page {
    unsigned long flags;
    union {
        struct { /* Page cache and anonymous pages */
            ...
            void* private;
        };
        struct { /* page_pool used by netstack */ ... };
        struct { /* Tail pages of compound page */ ... };
        ...
        struct { /* Page table pages */ ... };
    ... };
};
```

Bitmasks

Flags, cpumasks, etc.

Bitmasks are widely used to track attributes, types or parameters of various structs or routines, or even control flow of complex algorithms.

- ▶ Examples:
 - GFP mask - *include/linux/gfp_types.h*
 - dentry flags - *include/linux/dcache.h*
 - cpumasks - *include/linux/cpumask.h*

Context macros

Know where you are

The CPU knows certain context information. Kernel code can get it whenever needed:

- ▶ *#define current*
 - pointer to the `task_struct` of the currently executing process on *_this_* CPU
- ▶ *#define smp_processor_id()*
 - int number of the logical CPU where *_this_* code is executing

Per-cpu structs

Efficiency

To optimize access and remove the need for synchronized access, certain structures are created as **“per-cpu” copies**. The benefit is that each CPU has its own struct, so there’s no need for mutual exclusion.

- ▶ Each CPU has its “per-cpu offset”
- ▶ Per-cpu structs simply define a pointer/value that must be added to the per-cpu offset to get the pointer to the structure belonging to the specific CPU.

Basic Debugging

... ahh, not again ...

Kernel OOPS log

(Don't) panic

```

[ 5.396811] block dm-0: the capability attribute has been deprecated.
[514435.962056] oops_module: loading out-of-tree module taints kernel.
[514435.962106] oops_module: module verification failed: signature and/or required key missing - tainting kernel
[514480.714476] BUG: kernel NULL pointer dereference, address: 0000000000000000
[514480.714521] #PF: supervisor read access in kernel mode
[514480.714540] #PF: error_code(0x0000) - not-present page
[514480.714560] PGD 0 P4D 0
[514480.714575] Ooops: 0000 [#1] PREEMPT SMP NOPTI
[514480.714593] CPU: 0 PID: 132782 Comm: insmod Kdump: loaded Tainted: G          OE      -----   --- 5.14.0-427.35.1.el9_4.x86_64 #1
[514480.714643] Hardware name: QEMU Standard PC (Q35 + ICH9, 2009), BIOS 1.16.3-1.fc39 04/01/2014
[514480.714680] RIP: 0010:hello_init+0x5/0xff0 [oops_module]
[514480.714712] Code: Unable to access opcode bytes at RIP 0xffffffffc062efeb.
[514480.714731] RSP: 0018:ffffb29700f33d90 EFLAGS: 00010246
[514480.714747] RAX: 0000000000000000 RBX: 0000000000000000 RCX: 0000000000000001
[514480.714767] RDX: 0000000000000000 RSI: ffffffff883eac23 RDI: ffffffff062f010
[514480.714796] RBP: ffffffff062f010 R08: 0000000000000010 R09: 0000000000000000
[514480.714821] R10: ffff9dedd8466401 R11: 0000000000000000 R12: ffff9dedd7dbb700
[514480.714845] R13: fffff29700f33e28 R14: 0000000000000003 R15: 0000000000000000
[514480.714869] FS: 000073ff90fd740(0000) GS:ffff9dec37ce0000(0000) knlGS:0000000000000000
[514480.714895] CS: 0010 DS: 0000 ES: 0000 CR0: 0000000080050033
[514480.714915] CR2: ffffffff062efeb CR3: 00000001f98f6002 CR4: 000000000770ef0
[514480.714935] PKRU: 55555554
[514480.714945] Call Trace:
[514480.714955] <TASK>
[514480.714963] ? show_trace_log_lvl+0x1c4/0x2df
[514480.714980] ? show_trace_log_lvl+0x1c4/0x2df
[514480.714997] ? __pfx_init_module+0x10/0x10 [oops_module]
[514480.715014] ? do_one_initcall+0x41/0x210
[514480.715031] ? __die_body.cold+0x8/0xd
[514480.715043] ? page_fault_oops+0x134/0x170
[514480.715064] ? sysfs_add_file_mode_ns+0x85/0x150
[514480.715084] ? exc_page_fault+0x62/0x150
[514480.715101] ? asm_exc_page_fault+0x22/0x30
[514480.715124] ? __pfx_init_module+0x10/0x10 [oops_module]
[514480.715145] ? do_init_module+0x23/0x270
[514480.715163] ? __pfx_init_module+0x10/0x10 [oops_module]
[514480.715183] ? hello_init+0x5/0xff0 [oops_module]
[514480.715203] ? do_one_initcall+0x41/0x210
[514480.715220] ? kmalloc_trace+0x25/0xa0
[514480.715237] ? do_init_module+0x5c/0x270
[514480.715253] ? __do_sys_finit_module+0xae/0x110
[514480.715273] ? do_syscall_64+0x59/0x90
[514480.715289] ? syscall_exit_work+0x103/0x130
[514480.715308] ? syscall_exit_to_user_mode+0x22/0x40
[514480.715327] ? do_syscall_64+0x69/0x90
[514480.715342] ? exc_page_fault+0x62/0x150
[514480.715358] ? entry_SYSCALL_64_after_hwframe+0x72/0xdc
[514480.716062] RIP: 0033:0x73ff883ee5d
[514480.716757] Code: ff c3 66 2e 0f 1f 84 00 00 00 00 90 f3 0f 1e fa 48 89 f8 48 89 f7 48 89 d6 48 89 ca 4d 89 c2 4d 89 c8 4c 8b 4c 24 08 0f 05 <8> 3d 01 f0 ff ff 73 01 c3 48 8b 0d 93 af 1b 00 f7 d8 64 89 01 48
[514480.718322] RSP: 002b:00007fff667b4b98 EFLAGS: 00000246 ORIG_RAX: 0000000000000139
[514480.719053] RAX: ffffffff062f010 RBX: 00005d52ce407c0 RCX: 000073ff883ee5d
[514480.719532] RDX: 0000000000000000 RSI: 00005d52b360962 RDI: 0000000000000003
[514480.720019] RBP: 0000000000000000 R08: 0000000000000000 R09: 0000000000000000
[514480.720481] R10: 0000000000000003 R11: 0000000000000246 R12: 00005d52b360962
[514480.720963] R13: 00005d52ce43200 R14: 00005d52b35f550 R15: 00005d52ce408d0
[514480.721451] </TASK>
[514480.721915] Modules linked in: oops_module(OE+) tls nft_fib_inet nft_fib_ipv4 nft_fib_ipv6 nft_fib_nftables nft_reject_inet nf_defrag_ipv6 nf_defrag_ipv4 nf_tables nfnetlink sunrpc snd_hda_codec_generic ledtrig_audio snd_hda_intel intel_rapl_common snd_intel_dspcfg snd_intel_sdw_acpi intel_pmc_core intel_vsec pmt_telemetry pmt_class snd_hda_codec kvm_intel snd_hda_core snd_hwdep snd_seq snd_seq_dev ce snd_pcm kvm iTCO_wdt iTCO_vendor_support virtio_balloon snd_timer irqbypass rapl pcspkr snd_lpc_ich i2c_smbus soundcore i2c_smbus joydev xfs libcrc32c virtio_gpu virtio_dma_buf drm_shmem_helper drm_kms_helper crct10dif_pci libahci libahci crc32_pci libahci sysfillrect sysfillrect crc32c intel fb_sys_fops virtio_net net_failover libata drm failover virtio_console ghash_clmulni_intel virtio_scsi virtio_blk serio_raw dm_mirror dm_region_hash dm_log dm_mod fuse
[514480.724632] CR2: 0000000000000000

```

Kernel OOPS log

(Don't) panic

- ▶ Error message
- ▶ Oops record (depending on the error)
- ▶ Panic context - CPU, PID, command, kernel info
- ▶ Hardware info
- ▶ CPU registers' contents
- ▶ Call trace
- ▶ Modules linked in

Basic issues

(Don't) panic

- ▶ BUG() and WARN()
 - Macros that include a condition and produce log output on 'true';
BUG also panics...
 - Print exact file+line of code
- ▶ NULL pointer dereference
- ▶ General protection fault

Basic issues

(Don't) panic

Kernel has various *panic* options:

- ▶ `hung_task_panic`
When a process is in `UNinterruptible_sleep` longer than threshold
- ▶ `soft/hard lockup`
When the CPU doesn't reschedule (soft) / process interrupts (hard) for longer than `watchdog_thresh` (double for soft lockup)
- ▶ RCU stall
- ▶ OOM panic

Debugging approaches

At least some basic

- ▶ `echo 'h' > /proc/sysrq-trigger`
Instruct kernel to give you certain information... or panic
- ▶ `printk()`
Print stuff to kernel log, opt. with specific log-level
Ex.: `printk(KERN_INFO "My very informative message\n");`
- ▶ `kdump+vmcore` analysis
On kernel panic, there's a possibility to save a memory snapshot, which can be later analyzed.

Kexec, kdump, crash

The heavy weight

- ▶ kexec
 - Mechanism to boot into another kernel.
 - [-p] flag can specify a kernel to boot into on panic()
- ▶ kdump
 - A systemd service that automates kexec setup and further sets up the secondary (panic) kernel to save a memory snapshot (a *vmcore*)
- ▶ crash
 - A tool to open an analyze kernel vmcores

Kexec, kdump, crash

The heavy weight

- ▶ /etc/kdump.conf
 - dump target - *device & relative path*
 - core_collector*
- ▶ Kernel command line param: *crashkernel=*
- ▶ kdump.service
 - kdump initramfs
 - kexec -p
- ▶ ... Demo

Extra

If there's time left...

- ▶ Kernel processes
- ▶ VFS - virtual file system
- ▶ Control Groups [cgroups]

Thank you

Red Hat is the world's leading provider of enterprise open source software solutions. Award-winning support, training, and consulting services make Red Hat a trusted adviser to the Fortune 500.

 [linkedin.com/company/red-hat](https://www.linkedin.com/company/red-hat)

 [facebook.com/redhatinc](https://www.facebook.com/redhatinc)

 [youtube.com/user/RedHatVideos](https://www.youtube.com/user/RedHatVideos)

 twitter.com/RedHat

